## In the claims:

Please cancel claims 1-10, amend claim 11 as indicated, cancel claims 12-15, and add new claims 16-18. A listing of all claims is presented below:

Claims 1-10 (cancelled)

Claim 11 (currently amended): In a building structure,

a plurality of spaced apart footings,

a plurality of columns,

means supporting said columns on the respective feetings,

a column support for each of said columns supporting each of said

columns on a respective one of said footings,

a roof structure supported on said columns,

said roof structure having a flat, generally horizontal, upwardly facing surface surrounded by a border frame adapted to contain a pool of water, and,

said means supporting said columns on said respective feetings being vertically adjustable enabling said columns to support said reef structure in a position such that the flat surface is horizontal.

said flat, generally horizontal, upwardly facing surface and said border

frame defining a pool for containing water to a depth of approximately one inch or more,
and

water filling said pool to a depth of approximately one inch or more.

CM C

Claims 12-15 (cancelled)

Claim 16 (new): In the building structure of claim 11, wherein the column support for each of said columns comprises a column-supporting leveling plate above each of said footings, a plurality of bolts having lower portions embedded in, and upper portions projecting above, each of said footings, first nuts threaded on the upper portions of said bolts, said plates being supported on said first nuts, and second nuts threaded on the upper portions of said bolts and clamping said plates down on said first nuts.

Claim 17 (new): In the building structure of claim 16, wherein said footings are placed around a floor area of the building structure, a sub-floor extends over the floor area, and a finished floor extends over the sub-floor, said sub-floor, before installation of the finished floor, being adapted to receive weather-protected building and support materials and mobile equipment useful in the year-around construction of the building structure.

Claim 18 (new): In the building structure of claim 17, wherein said sub-floor is substantially horizontal except for a peripheral, marginal edge portion of said sub-floor which slopes downwardly in a direction away from the building structure to prevent frost by water accumulation.